

MARUKA

Our Goal is Your Success



CPC SERIES TUBE & PIPE BENDER SPECIFICATIONS

CPC Series

Single Axis NC Tube & Pipe Bender

CPC Series		CPC40	CPC60	CPC80	CPC100	CPC125
Bend Capacity	Steel pipe (thin wall)	42.7×3.5	60.5×5.5	89.1×4.2	114.3×4.5	165.2×7.1
	Steel pipe (thick wall)	27.2×5.5	42.7×6.4	60.5×8.7	76.3×9.5	101.6×12.7
Max		250	270	500	700	700
Effective mandrel length		1,300	1,850	2,800	5,500	5,500
NC Controller						
Number of NC control Axis		1	1	1	1	1
Number of programming process		9	9	9	9	9
Repeatability		±0.1°	±0.1°	±0.1°	±0.1°	±0.1°
Bend-arm speed (Sec / 180°)	High speed	2.5	5	7.5	15	30
	Low speed	4.5	7.5	11	26	50
Material / shape other than round pipe						
Electric motor (HP)		3	10	15	20	30
Weight		1,000	1,800	3,000	6,500	10,000
Option (special accessories)						

Unit: mm

Los Angeles Tech Center
16220 Manning Way
Cerritos, CA 90703
Tel: 562-926-3654
Fax: 562-630-0507

Kansas City Tech Center
1210 NE Douglas
Lee's Summit, MO 64086
Tel: 816-524-1811
Fax: 816-524-5444

Chicago Tech Center
1107 North Main Street
Lombard, IL 60148
Tel: 630-953-1707
Fax: 630-953-1753

New Jersey Tech Center
400 Commons Way, Suite 11
Rockaway, NJ 07866
Tel: 973-983-1000
Fax: 973-983-8711